



Lamps / LED

4.5W LED BLS 2 Pin - G23, 4000K

The LED BLL/BLS Lamps are an ideal replacement for old hat CFL technology. With a 5 year guarantee the LED BLL Lamps offer a cost-effective energy saving solution without the need to replace a complete fitting. Ideal for public buildings, offices, shops, supermarkets, hotels, restaurants and around the home.

- Energy saving benefits of LED without having to change fittings
- Aluminium heat sink for improved life
- True retrofit size
- High CRI
- Not suitable for emergency or dimming

Technical Specification

Product Code	04331
Reference	
Guarantee	5 Years
EAN	5013588043319
Commodity Code	85395000
Country Of Origin	CN
UNSPSC Code	39101628

www.belllighting.co.uk



This document is uncontrolled if printed, all information is subject to change. Generated on 5/4/2024 8:49:18 PM





Technical Specification

Watts (W)4.5CapG23Colour Temp (K)4000Dimmable?0Lumens (Im)405Life Hours45,000Energy RatingFCRI (Ra)85Switching Cycles20,000Energy Consumption (kWh/1000h)4.5DimensionsVidth (mm)Width (mm)32Length (mm)166Packaging Information37Single Carton Height (mm)37Single Carton Depth (mm)175Single Carton Weight (KG)0.044Individual Volume0.00016Outer Box Aty20Outer Box Height (mm)165Outer Box Depth (mm)190Outer Box Weight (kg)4.3	Volts (V)	240
Colour Temp (K)4000Dimmable?0Lumens (Im)405Life Hours45,000Energy RatingFCRI (Ra)85Switching Cycles20,000Energy Consumption (kWh/1000h)4.5Dimensions166Width (mm)32Length (mm)166Packaging Information37Single Carton Height (mm)37Single Carton Weight (KG)0.04Individual Volume0.00016Outer Box Qty20Outer Box Width (mm)190	Watts (W)	4.5
Dimmable?0Lumens (Im)405Life Hours45,000Energy RatingFCRI (Ra)85Switching Cycles20,000Energy Consumption (kWh/1000h)4.5DimensionsYWidth (mm)32Length (mm)166Packaging Information37Single Carton Height (mm)37Single Carton Depth (mm)175Single Carton Weight (KG)0.04Individual Volume0.00016Outer Box Width (mm)155Outer Box Width (mm)190	Сар	G23
Lumens (Im)405Life Hours45,000Energy RatingFCRI (Ra)85Switching Cycles20,000Energy Consumption (kWh/1000h)4.5Dimensions32Width (mm)32Length (mm)166Packaging Information37Single Carton Height (mm)37Single Carton Depth (mm)175Single Carton Weight (KG)0.04Individual Volume0.00016Outer Box Width (mm)155Outer Box Width (mm)190	Colour Temp (K)	4000
Life Hours45,000Energy RatingFCRI (Ra)85Switching Cycles20,000Energy Consumption (kWh/1000h)4.5DimensionsYWidth (mm)32Length (mm)166Packaging Information25Single Carton Height (mm)37Single Carton Depth (mm)175Single Carton Weight (KG)0.04Individual Volume0.00016Outer Box Qty20Outer Box Width (mm)155Outer Box Width (mm)190	Dimmable?	0
Energy RatingFCRI (Ra)85Switching Cycles20,000Energy Consumption (kWh/1000h)4.5Dimensions32Width (mm)32Length (mm)166Packaging Information25Single Carton Height (mm)37Single Carton Depth (mm)175Single Carton Width (KG)0.04Individual Volume0.00016Outer Box Qty20Outer Box Width (mm)155Outer Box Width (mm)190	Lumens (lm)	405
CRI (Ra)85Switching Cycles20,000Energy Consumption (kWh/1000h)4.5Dimensions32Width (mm)32Length (mm)166Packaging Information37Single Carton Height (mm)37Single Carton Depth (mm)175Single Carton Width (KG)0.04Individual Volume0.00016Outer Box Qty20Outer Box Width (mm)155Outer Box Width (mm)190	Life Hours	45,000
Switching Cycles20,000Energy Consumption (kWh/1000h)4.5Dimensions32Width (mm)32Length (mm)166Packaging Information25Single Carton Height (mm)37Single Carton Width (mm)175Single Carton Depth (mm)175Single Carton Weight (KG)0.04Individual Volume0.00016Outer Box Aty20Outer Box Height (mm)155Outer Box Width (mm)190	Energy Rating	F
Energy Consumption (kWh/1000h)4.5Dimensions32Width (mm)32Length (mm)166Packaging Information25Single Carton Height (mm)37Single Carton Width (mm)37Single Carton Depth (mm)175Single Carton Weight (KG)0.04Individual Volume0.00016Outer Box Qty20Outer Box Height (mm)155Outer Box Width (mm)190	CRI (Ra)	85
DimensionsWidth (mm)32Length (mm)166Packaging InformationSingle Carton Height (mm)25Single Carton Width (mm)37Single Carton Depth (mm)175Single Carton Weight (KG)0.04Individual Volume0.00016Outer Box Qty20Outer Box Height (mm)155Outer Box Width (mm)165Outer Box Depth (mm)190	Switching Cycles	20,000
Width (mm)32Length (mm)166Packaging InformationSingle Carton Height (mm)25Single Carton Width (mm)37Single Carton Depth (mm)175Single Carton Weight (KG)0.04Individual Volume0.00016Outer Box Qty20Outer Box Height (mm)155Outer Box Width (mm)165Outer Box Depth (mm)190	Energy Consumption (kWh/1000h)	4.5
Length (mm)166Packaging Information25Single Carton Height (mm)25Single Carton Width (mm)37Single Carton Depth (mm)175Single Carton Weight (KG)0.04Individual Volume0.00016Outer Box Qty20Outer Box Height (mm)155Outer Box Width (mm)165Outer Box Depth (mm)190	Dimensions	
Packaging InformationSingle Carton Height (mm)25Single Carton Width (mm)37Single Carton Depth (mm)175Single Carton Weight (KG)0.04Individual Volume0.00016Outer Box Qty20Outer Box Height (mm)155Outer Box Width (mm)165Outer Box Depth (mm)190	Width (mm)	32
Single Carton Height (mm)25Single Carton Width (mm)37Single Carton Depth (mm)175Single Carton Weight (KG)0.04Individual Volume0.00016Outer Box Qty20Outer Box Height (mm)155Outer Box Width (mm)165Outer Box Depth (mm)190	Length (mm)	166
Single Carton Width (mm)37Single Carton Depth (mm)175Single Carton Weight (KG)0.04Individual Volume0.00016Outer Box Qty20Outer Box Height (mm)155Outer Box Width (mm)165Outer Box Depth (mm)190	Packaging Information	
Single Carton Depth (mm)175Single Carton Weight (KG)0.04Individual Volume0.00016Outer Box Qty20Outer Box Height (mm)155Outer Box Width (mm)165Outer Box Depth (mm)190	Single Carton Height (mm)	25
Single Carton Weight (KG)0.04Individual Volume0.00016Outer Box Qty20Outer Box Height (mm)155Outer Box Width (mm)165Outer Box Depth (mm)190	Single Carton Width (mm)	37
Individual Volume0.00016Outer Box Qty20Outer Box Height (mm)155Outer Box Width (mm)165Outer Box Depth (mm)190	Single Carton Depth (mm)	175
Outer Box Qty20Outer Box Height (mm)155Outer Box Width (mm)165Outer Box Depth (mm)190	Single Carton Weight (KG)	0.04
Outer Box Height (mm)155Outer Box Width (mm)165Outer Box Depth (mm)190	Individual Volume	0.00016
Outer Box Width (mm)165Outer Box Depth (mm)190	Outer Box Qty	20
Outer Box Depth (mm) 190	Outer Box Height (mm)	155
	Outer Box Width (mm)	165
Outer Box Weight (kg) 4.3	Outer Box Depth (mm)	190
	Outer Box Weight (kg)	4.3

E: sales@belllighting.co.uk **T:** 01924 893380

www.belllighting.co.uk



This document is uncontrolled if printed, all information is subject to change. Generated on 5/4/2024 8:49:18 PM