



Lamps / LED

4W LED Filament Clear GLS - BC, 2700K (Upgraded Product – Order New Code: 60749)

The LED Filament Range combines LED technology with the elegance of Incandescent Lamps. Creating a welcoming atmosphere with a retro feel, our LED Filament Range offers smooth dimming on rotary and digital dimming systems. The Filament GLS is an all rounder for decorative applications due to the wide range of wattages we offer.

- LED Technology with the elegance of Incandescent Lamps
- Creates a welcoming atmosphere with retro feel
- Argon gas filled to improve life
- Smooth dimming on rotary and digital dimming systems
- Full glass envelope

Technical Specification

Product Code	05016
Reference	
Guarantee	3 Years
EAN	5013588050164
Commodity Code	8539520000
Country Of Origin	CN
UNSPSC Code	39101628

www.belllighting.co.uk



This document is uncontrolled if printed, all information is subject to change. Generated on 5/6/2024 2:54:41 PM





Technical Specification

Watts (W)4CapBC/B22Colour Temp (K)2700Dimmable?0Lumens (Im)470Life Hours15,000Beam Angle300°Energy RatingECRI (Ra)85Switching Cycles8,000Frequency (Hz)50/60LED Drive Current22Energy Consumption (kWh/1000h)4Dimensions102Height (mm)102Diameter (mm)60
Colour Temp (K)2700Dimmable?0Lumens (Im)470Life Hours15,000Beam Angle300°Energy RatingECRI (Ra)85Switching Cycles8,000Frequency (Hz)50/60LED Drive Current22Energy Consumption (kWh/1000h)4Dimensions102Height (mm)102Diameter (mm)60
Dimmable?0Lumens (lm)470Life Hours15,000Beam Angle300°Energy RatingECRI (Ra)85Switching Cycles8,000Frequency (Hz)50/60LED Drive Current22Energy Consumption (kWh/1000h)4Dimensions102Height (mm)102Diameter (mm)60
Lumens (Im)470Life Hours15,000Beam Angle300°Energy RatingECRI (Ra)85Switching Cycles8,000Frequency (Hz)50/60LED Drive Current22Energy Consumption (kWh/1000h)4Dimensions102Height (mm)102Diameter (mm)60
Life Hours15,000Beam Angle300°Energy RatingECRI (Ra)85Switching Cycles8,000Frequency (Hz)50/60LED Drive Current22Energy Consumption (kWh/1000h)4Dimensions102Height (mm)102Diameter (mm)60
Beam Angle300°Energy RatingECRI (Ra)85Switching Cycles8,000Frequency (Hz)50/60LED Drive Current22Energy Consumption (kWh/1000h)4Dimensions102Height (mm)102Diameter (mm)60
Energy RatingECRI (Ra)85Switching Cycles8,000Frequency (Hz)50/60LED Drive Current22Energy Consumption (kWh/1000h)4Dimensions102Height (mm)102Diameter (mm)60
CRI (Ra)85Switching Cycles8,000Frequency (Hz)50/60LED Drive Current22Energy Consumption (kWh/1000h)4Dimensions102Height (mm)102Diameter (mm)60
Switching Cycles8,000Frequency (Hz)50/60LED Drive Current22Energy Consumption (kWh/1000h)4Dimensions102Height (mm)102Diameter (mm)60
Frequency (Hz)50/60LED Drive Current22Energy Consumption (kWh/1000h)4Dimensions102Height (mm)102Diameter (mm)60
LED Drive Current22Energy Consumption (kWh/1000h)4Dimensions102Height (mm)102Diameter (mm)60
Energy Consumption (kWh/1000h)4DimensionsHeight (mm)102Diameter (mm)60
Dimensions Height (mm) 102 Diameter (mm) 60
Height (mm)102Diameter (mm)60
Diameter (mm) 60
Packaging Information
Single Carton Height (mm) 125
Single Carton Width (mm)65
Single Carton Depth (mm)65
Single Carton Weight (KG)0.05
Individual Volume 0.00053
Inner Box Qty 10
Inner Box Height (mm) 140
Inner Box Width (mm) 340
Inner Box Depth (mm) 140
Inner Box Weight (kg) 0.65
Outer Box Qty 100
Outer Box Height (mm) 675
Outer Box Height (mm) 675

E: sales@belllighting.co.uk **T:** 01924 893380

www.belllighting.co.uk



This document is uncontrolled if printed, all information is subject to change. Generated on 5/6/2024 2:54:41 PM