



## Lamps / LED

## 6W LED Filament Clear GLS - BC, 2700K (Upgraded Product – Order New Code: 60751)



The LED Filament Range combines LED technology with the elegance of Incandescent Lamps. Creating a welcoming atmosphere with a retro feel, our LED Filament Range offers smooth dimming on rotary and digital dimming systems. The Filament GLS is an all rounder for decorative applications due to the wide range of wattages we offer.

- LED Technology with the elegance of Incandescent Lamps
- Creates a welcoming atmosphere with retro feel
- Argon gas filled to improve life
- Smooth dimming on rotary and digital dimming systems
- Full glass envelope

## **Technical Specification**

Product Code	05018
Reference	
Guarantee	3 Years
EAN	5013588050188
Commodity Code	8539520000
Country Of Origin	CN
UNSPSC Code	39101628

www.belllighting.co.uk



This document is uncontrolled if printed, all information is subject to change. Generated on 4/28/2024 9:31:27 PM





## **Technical Specification**

Watts (W)6CapBC/B22Colour Temp (K)2700Dimmable?0Lumens (lm)810Life Hours15,000Beam Angle300°Energy RatingECRI (Ra)85Switching Cycles8,000Frequency (Hz)50/60LED Drive Current35Energy Consumption (kWh/1000h)6Dimensions102
Colour Temp (K)2700Dimmable?0Lumens (Im)810Life Hours15,000Beam Angle300°Energy RatingECRI (Ra)85Switching Cycles8,000Frequency (Hz)50/60LED Drive Current35Energy Consumption (kWh/1000h)6
Dimmable?0Lumens (Im)810Life Hours15,000Beam Angle300°Energy RatingECRI (Ra)85Switching Cycles8,000Frequency (Hz)50/60LED Drive Current35Energy Consumption (kWh/1000h)6Dimensions
Lumens (Im)810Life Hours15,000Beam Angle300°Energy RatingECRI (Ra)85Switching Cycles8,000Frequency (Hz)50/60LED Drive Current35Energy Consumption (kWh/1000h)6Dimensions
Life Hours15,000Beam Angle300°Energy RatingECRI (Ra)85Switching Cycles8,000Frequency (Hz)50/60LED Drive Current35Energy Consumption (kWh/1000h)6Dimensions
Beam Angle300°Energy RatingECRI (Ra)85Switching Cycles8,000Frequency (Hz)50/60LED Drive Current35Energy Consumption (kWh/1000h)6Dimensions
Energy RatingECRI (Ra)85Switching Cycles8,000Frequency (Hz)50/60LED Drive Current35Energy Consumption (kWh/1000h)6Dimensions
CRI (Ra)85Switching Cycles8,000Frequency (Hz)50/60LED Drive Current35Energy Consumption (kWh/1000h)6Dimensions
Switching Cycles8,000Frequency (Hz)50/60LED Drive Current35Energy Consumption (kWh/1000h)6Dimensions
Frequency (Hz)50/60LED Drive Current35Energy Consumption (kWh/1000h)6Dimensions
LED Drive Current35Energy Consumption (kWh/1000h)6Dimensions
Energy Consumption (kWh/1000h) 6   Dimensions 6
Dimensions
Height (mm) 102
Diameter (mm) 60
Packaging Information
Single Carton Height (mm)12.5
Single Carton Width (mm)6.5
Single Carton Depth (mm) 6.5
Single Carton Weight (KG) 0.05
Individual Volume 0.00053
Inner Box Qty 10
Inner Box Height (mm) 14
Inner Box Width (mm) 34
Inner Box Depth (mm) 14
Inner Box Weight (kg) 0.65
Inner Box Weight (kg)   0.65     Outer Box Qty   100
Outer Box Qty 100
Outer Box Qty100Outer Box Height (mm)29

**E:** sales@belllighting.co.uk **T:** 01924 893380

www.belllighting.co.uk



This document is uncontrolled if printed, all information is subject to change. Generated on 4/28/2024 9:31:27 PM