



Fittings / LED Floodlights

450W Skyline Elite + Asymmetric LED Floodlight -4000K (Type 3)



Skyline Elite+ represents the latest technology in sports floodlighting. Modern aesthetic, die-cast aluminium construction. With IP66 and low windage ratings this unit can handle the worst weather conditions. Perfect for large external sports facilities or industrial applications, complete with a fully adjustable mounting bracket.

- Genuine replacement for up to 1500W Metal Halide Floodlight
- Perfect for sports, building facade's, landscape, security & car park lighting
- Asymmetric distribution, low light pollution
- Up to 145 Lm/W
- Fully encapsulated IP66 TUV certified driver

Technical Specification

Product Code	08871
Reference	
Guarantee	10 Years
EAN	5013588088716
Commodity Code	9405409990
Country Of Origin	CN
UNSPSC Code	39111626

www.belllighting.co.uk



This document is uncontrolled if printed, all information is subject to change. Generated on 5/3/2024 9:40:58 AM





Technical Specification

Watts (W)450Colour Temp (K)4000Dimmable?1Lumens (Im)62250Life Hours70,000CRI (Ra)80Switching Cycles100,000Frequency (Hz)50/60LED Drive Current155Energy Consumption (kWh/1000h)450IP RatingIP66Dimensions104Width (mm)601Length (mm)621Packaging Information820Single Carton Height (mm)820Single Carton Depth (mm)185Single Carton Weight (KG)22Individual Volume0.11074Outer Box Qty2	Volts (V)	100-277
Dimmable?1Lumens (Im)62250Life Hours70,000CRI (Ra)80Switching Cycles100,000Frequency (Hz)50/60LED Drive Current155Energy Consumption (kWh/1000h)450IP RatingIP66Dimensions104Width (mm)601Length (mm)621Packaging Information820Single Carton Height (mm)185Single Carton Weight (KG)22Individual Volume0.11074	Watts (W)	450
Lumens (Im)62250Life Hours70,000CRI (Ra)80Switching Cycles100,000Frequency (Hz)50/60LED Drive Current155Energy Consumption (kWh/1000h)450IP RatingIP66DimensionsHeight (mm)104Width (mm)601Length (mm)621Packaging InformationSingle Carton Height (mm)730Single Carton Depth (mm)185Single Carton Weight (KG)22Individual Volume0.11074	Colour Temp (K)	4000
Life Hours70,000CRI (Ra)80Switching Cycles100,000Frequency (Hz)50/60LED Drive Current155Energy Consumption (kWh/1000h)450IP RatingIP66DimensionsHeight (mm)104Width (mm)601Length (mm)621Packaging InformationSingle Carton Height (mm)820Single Carton Depth (mm)185Single Carton Weight (KG)22Individual Volume0.11074	Dimmable?	1
CRI (Ra)80Switching Cycles100,000Frequency (Hz)50/60LED Drive Current155Energy Consumption (kWh/1000h)450IP RatingIP66Dimensions104Width (mm)601Length (mm)621Packaging Information820Single Carton Height (mm)185Single Carton Depth (mm)185Single Carton Weight (KG)22Individual Volume0.11074	Lumens (lm)	62250
Switching Cycles100,000Frequency (Hz)50/60LED Drive Current155Energy Consumption (kWh/1000h)450IP RatingIP66Dimensions104Width (mm)601Length (mm)621Packaging Information820Single Carton Height (mm)730Single Carton Depth (mm)185Single Carton Weight (KG)22Individual Volume0.11074	Life Hours	70,000
Frequency (Hz)50/60LED Drive Current155Energy Consumption (kWh/1000h)450IP RatingIP66Dimensions104Width (mm)601Length (mm)621Packaging Information820Single Carton Height (mm)820Single Carton Width (mm)185Single Carton Weight (KG)22Individual Volume0.11074	CRI (Ra)	80
LED Drive Current155Energy Consumption (kWh/1000h)450IP RatingIP66DimensionsI04Width (mm)601Length (mm)621Packaging Information820Single Carton Height (mm)730Single Carton Depth (mm)185Single Carton Width (KG)22Individual Volume0.11074	Switching Cycles	100,000
Energy Consumption (kWh/1000h)450IP RatingIP66DimensionsI04Width (mm)601Length (mm)621Packaging Information820Single Carton Height (mm)820Single Carton Width (mm)730Single Carton Depth (mm)185Single Carton Weight (KG)22Individual Volume0.11074	Frequency (Hz)	50/60
IP RatingIP66Dimensions104Height (mm)104Width (mm)601Length (mm)621Packaging Information820Single Carton Height (mm)820Single Carton Width (mm)730Single Carton Depth (mm)185Single Carton Weight (KG)22Individual Volume0.11074	LED Drive Current	155
DimensionsHeight (mm)104Width (mm)601Length (mm)621Packaging Information820Single Carton Height (mm)820Single Carton Width (mm)730Single Carton Depth (mm)185Single Carton Weight (KG)22Individual Volume0.11074	Energy Consumption (kWh/1000h)	450
Height (mm)104Width (mm)601Length (mm)621Packaging Information820Single Carton Height (mm)820Single Carton Width (mm)730Single Carton Depth (mm)185Single Carton Weight (KG)22Individual Volume0.11074	IP Rating	IP66
Width (mm)601Length (mm)621Packaging Information820Single Carton Height (mm)820Single Carton Width (mm)730Single Carton Depth (mm)185Single Carton Weight (KG)22Individual Volume0.11074	Dimensions	
Length (mm)621Packaging Information820Single Carton Height (mm)820Single Carton Width (mm)730Single Carton Depth (mm)185Single Carton Weight (KG)22Individual Volume0.11074	Height (mm)	104
Packaging InformationSingle Carton Height (mm)820Single Carton Width (mm)730Single Carton Depth (mm)185Single Carton Weight (KG)22Individual Volume0.11074	Width (mm)	601
Single Carton Height (mm)820Single Carton Width (mm)730Single Carton Depth (mm)185Single Carton Weight (KG)22Individual Volume0.11074	Length (mm)	621
Single Carton Width (mm)730Single Carton Depth (mm)185Single Carton Weight (KG)22Individual Volume0.11074	Packaging Information	
Single Carton Depth (mm)185Single Carton Weight (KG)22Individual Volume0.11074	Single Carton Height (mm)	820
Single Carton Weight (KG)22Individual Volume0.11074	Single Carton Width (mm)	730
Individual Volume 0.11074	Single Carton Depth (mm)	185
	Single Carton Weight (KG)	22
Outer Box Qty 2	Individual Volume	0.11074
	Outer Box Qty	2

www.belllighting.co.uk



This document is uncontrolled if printed, all information is subject to change. Generated on 5/3/2024 9:40:58 AM