

## Fittings / LED Warehouse Lighting

### 150W-200W Illumina Slim Switchable Elite LED High Bay - Emergency, 120° Lens, 4000K

The Illumina Slim Elite luminaire is our most efficient High Bay. A versatile LED fitting, ideally suited to a wide range of industrial applications for both new installations and retrofit applications.

- Seoul Semiconductor LED
- Integrated microwave sensor versions available
- High CRI Ra85
- TUV Driver
- Wattage Switchable

## Technical Specification

|              |       |
|--------------|-------|
| Product Code | 08891 |
|--------------|-------|

### Reference

|                   |               |
|-------------------|---------------|
| Guarantee         | 7 Years       |
| EAN               | 5013588088914 |
| Commodity Code    | 9405423990    |
| Country Of Origin | CN            |
| UNSPSC Code       | 39111546      |

## Technical Specification

|                                |             |
|--------------------------------|-------------|
| Volts (V)                      | 220-240     |
| Watts (W)                      | 150-200     |
| Colour Temp (K)                | 4000        |
| Dimmable?                      | 0           |
| Lumens (lm)                    | 30000-39200 |
| Life Hours                     | 50,000      |
| Beam Angle                     | 120°        |
| CRI (Ra)                       | 80          |
| Switching Cycles               | 100,000     |
| Frequency (Hz)                 | 50/60       |
| LED Drive Current              | 45          |
| Energy Consumption (kWh/1000h) | 200         |
| IP Rating                      | IP65        |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 167 |
| Diameter (mm) | 364 |

## Packaging Information

|                           |         |
|---------------------------|---------|
| Single Carton Height (mm) | 430     |
| Single Carton Width (mm)  | 430     |
| Single Carton Depth (mm)  | 170     |
| Single Carton Weight (KG) | 4.5     |
| Individual Volume         | 0.03143 |