

Fittings / LED Panels

36W Arial Backlit High Output UGR <19 LED Panel - 600x600mm, White, 4000K

The Arial Plus is our leading panel when it comes to performance. With a high lumen output of over 120 lumens per watt, this panel is ideal for areas that require high lux levels. The Arial Plus can be installed in areas where TPa rated lighting products are essential, such as emergency exit routes including stairways and corridors.

- High efficiency
- TPa
- Uniform light distribution
- Professional LED Panel
- Anti-twist frame

Technical Specification

| | |
|--------------|-------|
| Product Code | 10140 |
|--------------|-------|

Reference

| | |
|-------------------|---------------|
| Guarantee | 7 Years |
| EAN | 5013588101408 |
| Commodity Code | 9405409990 |
| Country Of Origin | CN |
| UNSPSC Code | 39111544 |

Technical Specification

| | |
|------------------|---------|
| Volts (V) | 220-240 |
| Watts (W) | 36 |
| Colour Temp (K) | 4000 |
| Dimmable? | 0 |
| Lumens (lm) | 3841 |
| Life Hours | 50,000 |
| CRI (Ra) | >80 |
| Switching Cycles | 25,000 |
| Frequency (Hz) | 50/60 |
| IP Rating | IP20 |

Dimensions

| | |
|-------------|-----|
| Height (mm) | 595 |
| Width (mm) | 595 |
| Depth (mm) | 32 |

Packaging Information

| | |
|---------------------------|---------|
| Single Carton Height (mm) | 655 |
| Single Carton Width (mm) | 52 |
| Single Carton Depth (mm) | 648 |
| Single Carton Weight (KG) | 2.2 |
| Individual Volume | 0.02207 |
| Inner Box Qty | 1 |
| Outer Box Qty | 5 |
| Outer Box Height (mm) | 675 |
| Outer Box Width (mm) | 290 |
| Outer Box Depth (mm) | 660 |