



## Fittings / LED Panels

36W Arial Backlit High Output UGR <19 LED Panel - 600x600mm, Emergency, White (5 Year Battery Guarantee), 4000K

> The Arial Plus is our leading panel when it comes to performance. With a high lumen output of over 120 lumens per watt, this panel is ideal for areas that require high lux levels. The Arial Plus can be installed in areas where TPa rated lighting products are essential, such as emergency exit routes including stairways and corridors.

- High efficiency
- TPa
- Uniform light distribution
- Professional LED Panel
- Anti-twist frame

## **Technical Specification**

Product Code	10141
Reference	
Guarantee	7 Years
EAN	5013588101415
Commodity Code	9405409990
Country Of Origin	CN
UNSPSC Code	39111544

www.belllighting.co.uk



This document is uncontrolled if printed, all information is subject to change. Generated on 5/3/2024 8:41:53 PM





## **Technical Specification**

Volts (V)	220-240
Watts (W)	36
Colour Temp (K)	4000
Dimmable?	0
Lumens (lm)	3841
Life Hours	50,000
CRI (Ra)	>80
Switching Cycles	25,000
Frequency (Hz)	50/60
IP Rating	IP20
Dimensions	
	505
Height (mm)	595
Width (mm)	595
Depth (mm)	32
Packaging Information	
Single Carton Height (mm)	655
Single Carton Width (mm)	648
Single Carton Depth (mm)	52
Single Carton Weight (KG)	3.7
Individual Volume	0.02207
Inner Box Qty	1
Outer Box Qty	50
Outer Box Height (mm)	675
Outer Box Width (mm)	660
Outer Box Depth (mm)	66

**E:** sales@belllighting.co.uk **T:** 01924 893380

www.belllighting.co.uk



This document is uncontrolled if printed, all information is subject to change. Generated on 5/3/2024 8:41:53 PM