



Fittings / LED Panels

36W Arial Backlit High Output UGR <19 LED Panel - 600x600mm, White, Dali Dim, 4000K



The Arial Plus is our leading panel when it comes to performance. With a high lumen output of over 120 lumens per watt, this panel is ideal for areas that require high lux levels. The Arial Plus can be installed in areas where TPa rated lighting products are essential, such as emergency exit routes including stairways and corridors.

- High efficiency
- TPa
- Uniform light distribution
- Professional LED Panel
- Anti-twist frame

Technical Specification

Product Code	10143
Reference	
Guarantee	7 Years
EAN	5013588101439
Commodity Code	9405409990
Country Of Origin	CN
UNSPSC Code	39111544

www.belllighting.co.uk



This document is uncontrolled if printed, all information is subject to change. Generated on 4/28/2024 10:47:35 PM





Technical Specification

Volts (V)	220-240
Watts (W)	36
Colour Temp (K)	4000
Dimmable?	1
Lumens (lm)	3841
Life Hours	50,000
CRI (Ra)	>80
Switching Cycles	25,000
Frequency (Hz)	50/60
IP Rating	IP20
Dimensions	
Height (mm)	595
Width (mm)	595
Depth (mm)	32
Packaging Information	
Single Carton Height (mm)	65.5
Single Carton Width (mm)	5.2
Single Carton Depth (mm)	64.8
Single Carton Weight (KG)	2.2
Individual Volume	0.02207
Inner Box Qty	1
Outer Box Qty	5
Outer Box Height (mm)	67.5
Outer Box Width (mm)	29
Outer Box Depth (mm)	66
Outer Box CMB	0.1292

www.belllighting.co.uk



This document is uncontrolled if printed, all information is subject to change. Generated on 4/28/2024 10:47:35 PM