

## Fittings / LED Battens

### 20W Ultra LED Integrated Batten - 4000K, Single with Microwave Sensor 1230mm (4ft)



The Ultra Batten is a versatile general-purpose luminaire. With a sleek look, this Ultra Batten is an ideal candidate for office, classroom and corridor installations. Offered in 4, 5 & 6ft lengths, and boasting a 7 year guarantee with a 2 year on site warranty.

- The smart replacement for Single/Twin Fluorescent T8 and T5 Fixtures
- Special high light transmission frosted polycarbonate diffuser for smooth uniform lighting
- Tool-free termination
- Integrated controls
- Shatterproof

## Technical Specification

|              |       |
|--------------|-------|
| Product Code | 10202 |
|--------------|-------|

### Reference

|                   |               |
|-------------------|---------------|
| Guarantee         | 7 Years       |
| EAN               | 5013588102023 |
| Commodity Code    | 94054099      |
| Country Of Origin | CN            |
| UNSPSC Code       | 39111544      |

## Technical Specification

|                                |         |
|--------------------------------|---------|
| Volts (V)                      | 220-240 |
| Watts (W)                      | 20      |
| Colour Temp (K)                | 4000    |
| Dimmable?                      | 0       |
| Lumens (lm)                    | 2850    |
| Candelas (cd)                  | 650     |
| Life Hours                     | 50,000  |
| Beam Angle                     | 156°    |
| CRI (Ra)                       | 85      |
| Switching Cycles               | 25,000  |
| Frequency (Hz)                 | 50/60   |
| LED Drive Current              | 480     |
| Energy Consumption (kWh/1000h) | 20      |
| IP Rating                      | IP20    |

## Dimensions

|             |       |
|-------------|-------|
| Height (mm) | 82    |
| Width (mm)  | 69    |
| Length (mm) | 1,230 |

## Packaging Information

|                           |         |
|---------------------------|---------|
| Single Carton Height (mm) | 1240    |
| Single Carton Width (mm)  | 90      |
| Single Carton Depth (mm)  | 75      |
| Single Carton Weight (KG) | 1.58    |
| Individual Volume         | 0.00787 |
| Outer Box Qty             | 10      |
| Outer Box Height (mm)     | 1250    |
| Outer Box Width (mm)      | 250     |
| Outer Box Depth (mm)      | 210     |
| Outer Box Weight (kg)     | 10.47   |
| Outer Box CMB             | 0.07    |