



Fittings / LED Battens

50W Ultra LED Integrated Batten - 4000K, Single Emergency 1795mm (6ft)

The Ultra Batten is a versatile general-purpose luminaire. With a sleek look, this Ultra Batten is an ideal candidate for office, classroom and corridor installations. Offered in 4, 5 & 6ft lengths, and boasting a 7 year guarantee with a 2 year on site warranty.

- The smart replacement for Single/Twin Fluorescent T8 and T5 Fixtures
- Special high light transmission frosted polycarbonate diffuser for smooth uniform lighting
- Tool-free termination
- Integrated controls
- Shatterproof

Technical Specification

| Product Code | 10225 |
|--------------|-------|
| | |

Reference

| Guarantee | 7 Years |
|-------------------|---------------|
| EAN | 5013588102252 |
| Commodity Code | 9405409990 |
| Country Of Origin | CN |
| UNSPSC Code | 39111544 |
| | |









Technical Specification

| Volts (V) | 220-240 |
|--------------------------------|---------|
| Watts (W) | 50 |
| Colour Temp (K) | 4000 |
| Dimmable? | 0 |
| Lumens (lm) | 6350 |
| Candelas (cd) | 1,500 |
| Life Hours | 50,000 |
| Beam Angle | 116° |
| CRI (Ra) | 85 |
| Switching Cycles | 25,000 |
| Frequency (Hz) | 50/60 |
| LED Drive Current | 1,320 |
| Energy Consumption (kWh/1000h) | 50 |
| IP Rating | IP20 |
| Dimensions | |
| Height (mm) | 82 |
| Width (mm) | 69 |
| Length (mm) | 1,795 |
| Packaging Information | |
| Single Carton Height (mm) | 86 |
| Single Carton Width (mm) | 74 |
| Single Carton Depth (mm) | 1800 |
| Individual Volume | 0.01146 |
| Outer Box Qty | 4 |
| Outer Box Height (mm) | 180 |
| Outer Box Width (mm) | 200 |
| Outer box Width (IIIII) | 200 |
| Outer Box Depth (mm) | 182 |

E: sales@belllighting.co.uk **T:** 01924 893380

