

Fittings / Downlights

6W Firestay LED Integrated Fixed Downlight, Incl White & Satin Bezel - 4000K, 60° Beam Angle - Plug & Play Fitting



The Firestay Integrated Fixed Downlight boasts a 5 year guarantee and is supplied with white & satin bezels as standard.

- Firestay Certification: 30, 60 and 90 minute solid joist ceilings, 30 minute I-Joist & metal web ceiling systems
- IP65
- Part B/C/E compliant
- White bezel & magnetic satin bezel
- Part L compliant

Technical Specification

Product Code	10498
--------------	-------

Reference

Guarantee	3 Years
EAN	5013588104980
Commodity Code	94054099
Country Of Origin	CN
UNSPSC Code	39111515

Technical Specification

Volts (V)	220-240
Watts (W)	6
Colour Temp (K)	4000
Dimmable?	1
Lumens (lm)	595
Candelas (cd)	1,200
Life Hours	35,000
Beam Angle	60°
CRI (Ra)	>80
Switching Cycles	10,000
Frequency (Hz)	50/60
Energy Consumption (kWh/1000h)	6
IP Rating	IP65

Dimensions

Width (mm)	53.5
Depth (mm)	68.9
Diameter (mm)	80.6
Downlight Cut Out (mm)	60-70

Packaging Information

Single Carton Height (mm)	8.5
Single Carton Width (mm)	8.6
Single Carton Depth (mm)	9.8
Single Carton Weight (KG)	0.28
Individual Volume	0.00072
Inner Box Qty	10
Inner Box Height (mm)	45
Inner Box Width (mm)	21
Inner Box Depth (mm)	10
Inner Box Weight (kg)	3
Outer Box Qty	20
Outer Box Height (mm)	46.5
Outer Box Width (mm)	22.5
Outer Box Depth (mm)	22.5
Outer Box CMB	0.02