

Fittings / Downlights

6W Firestay LED Integrated Fixed Downlight, Incl White & Satin Bezel - 2700K, 40° Beam Angle - Plug & Play Fitting

The Firestay Integrated Fixed Downlight boasts a 5 year guarantee and is supplied with white & satin bezels as standard.

- Firestay Certification: 30, 60 and 90 minute solid joist ceilings, 30 minute I-Joist & metal web ceiling systems
- IP65
- Part B/C/E compliant
- White bezel & magnetic satin bezel
- Part L compliant

Technical Specification

Product Code	10499
--------------	-------

Reference

Guarantee	3 Years
EAN	5013588104997
Commodity Code	9405409990
Country Of Origin	CN
UNSPSC Code	39111515

Technical Specification

Volts (V)	220-240
Watts (W)	6
Colour Temp (K)	2700
Dimmable?	1
Lumens (lm)	575
Candelas (cd)	1,050
Life Hours	35,000
Beam Angle	40°
CRI (Ra)	>80
Switching Cycles	10,000
Frequency (Hz)	50/60
Energy Consumption (kWh/1000h)	6
IP Rating	IP65

Dimensions

Width (mm)	53.5
Depth (mm)	68.9
Diameter (mm)	80.6
Downlight Cut Out (mm)	60-70

Packaging Information

Single Carton Height (mm)	98
Single Carton Width (mm)	86
Single Carton Depth (mm)	85
Single Carton Weight (KG)	0.28
Individual Volume	0.00072
Inner Box Qty	10
Inner Box Height (mm)	446
Inner Box Width (mm)	207
Inner Box Depth (mm)	96
Inner Box Weight (kg)	2.95
Outer Box Qty	20
Outer Box Height (mm)	466
Outer Box Width (mm)	230
Outer Box Depth (mm)	230
Outer Box Weight (kg)	6.2