

## Fittings / Downlights

### Fire Rated MV/LV Showerlight - White

The Firestay Non Integrated Downlight gives you the freedom to choose your lamp without the need to replace the complete fitting. Available as Fixed, Centre Tilt & IP65 Showerlight with a choice of finishes and accessories.

- Firestay Certification: 30, 60 and 90 minute solid joist ceilings, 30 minute I-Joist ceiling systems
- Part B/C/E compliant
- Part L compliant with BELL Halo Elite/Halo Glass LED GU10
- Fixed / Centre Tilt / Showerlight IP65 Downlights
- Suitable for 240V lamps (GU10 lamp holder included)

## Technical Specification

Product Code	10650
--------------	-------

### Reference

Guarantee	5 Years
EAN	5013588106502
Commodity Code	9405409990
Country Of Origin	CN
UNSPSC Code	39111515

### Technical Specification

Volts (V)	240
Cap	GU10
Dimmable?	0
Frequency (Hz)	50
IP Rating	IP65

## Dimensions

Height (mm)	100
Width (mm)	93
Depth (mm)	96
Length (mm)	134
Diameter (mm)	85
Downlight Cut Out (mm)	68

## Packaging Information

Single Carton Height (mm)	78
Single Carton Width (mm)	105
Single Carton Depth (mm)	92
Single Carton Weight (KG)	0.22
Individual Volume	0.00075
Outer Box Qty	6
Outer Box Height (mm)	415
Outer Box Width (mm)	480
Outer Box Depth (mm)	225
Outer Box Weight (kg)	12.18