

## Fittings / Downlights

### Fire Rated MV/LV Centre Tilt - Antique Brass



The Firestay Non Integrated Downlight gives you the freedom to choose your lamp without the need to replace the complete fitting. Available as Fixed, Centre Tilt & IP65 Showerlight with a choice of finishes and accessories.

- Firestay Certification: 30, 60 and 90 minute solid joist ceilings, 30 minute I-Joist ceiling systems
- Part B/C/E compliant
- Part L compliant with BELL Halo Elite/Halo Glass LED GU10
- Fixed / Centre Tilt / Showerlight IP65 Downlights
- Suitable for 240V lamps (GU10 lamp holder included)

## Technical Specification

Product Code	10658
--------------	-------

### Reference

Guarantee	5 Years
EAN	5013588106588
Commodity Code	94054099
Country Of Origin	CN
UNSPSC Code	39111515

### Technical Specification

Volts (V)	240
Cap	GU10
Dimmable?	0
Frequency (Hz)	50
IP Rating	IP20

## Dimensions

Height (mm)	102
Width (mm)	96
Depth (mm)	94
Length (mm)	138
Diameter (mm)	87
Downlight Cut Out (mm)	78

## Packaging Information

Single Carton Height (mm)	7.8
Single Carton Width (mm)	10.5
Single Carton Depth (mm)	8.9
Single Carton Weight (KG)	0.7
Individual Volume	0.00073
Outer Box Qty	50
Outer Box Height (mm)	41.5
Outer Box Width (mm)	48
Outer Box Depth (mm)	22.5
Outer Box CMB	0.04482