

Fittings / Downlights

5W Firestay Slim Integrated Fixed Downlight White - 3000K

The most cost effective integrated downlight in the BELL range, the Firestay Slim comes with a 3 year quality guarantee. Fixed and Centre Tilt options available with a choice of finishes and colour temperatures.

- Firestay Certification: 30, 60 and 90 minute solid joist ceilings, 30 minute I-Joist & Metal Web ceiling systems
- IP65 - Fixed Versions / IP44 - Tilt Version
- Cut Out Ø55-68 mm
- Part B/C/E compliant
- Dimmable

Technical Specification

Product Code	10675
--------------	-------

Reference

Guarantee	3 Years
EAN	5013588106755
Commodity Code	9405409990
Country Of Origin	CN
UNSPSC Code	39111515

Technical Specification

Volts (V)	220-240
Watts (W)	5
Colour Temp (K)	3000
Dimmable?	1
Lumens (lm)	500
Life Hours	35,000
Beam Angle	60°
CRI (Ra)	80
Frequency (Hz)	50
LED Drive Current	14
Energy Consumption (kWh/1000h)	5
IP Rating	IP65

Dimensions

Height (mm)	82
Width (mm)	88
Depth (mm)	76
Length (mm)	125
Diameter (mm)	80
Downlight Cut Out (mm)	60

Packaging Information

Single Carton Height (mm)	90
Single Carton Width (mm)	90
Single Carton Depth (mm)	100
Single Carton Weight (KG)	0.28
Individual Volume	0.00081
Inner Box Qty	10
Inner Box Height (mm)	470
Inner Box Width (mm)	192
Inner Box Depth (mm)	110
Inner Box Weight (kg)	3
Outer Box Qty	20
Outer Box Height (mm)	490
Outer Box Width (mm)	212
Outer Box Depth (mm)	255
Outer Box Weight (kg)	6.3