

Fittings / Downlights

5W Firestay Slim Integrated Fixed Downlight Satin - 3000K



The most cost effective integrated downlight in the BELL range, the Firestay Slim comes with a 3 year quality guarantee. Fixed and Centre Tilt options available with a choice of finishes and colour temperatures.

- Firestay Certification: 30, 60 and 90 minute solid joist ceilings, 30 minute I-Joist & Metal Web ceiling systems
- IP65 - Fixed Versions / IP44 - Tilt Version
- Cut Out Ø55-68 mm
- Part B/C/E compliant
- Dimmable

Technical Specification

Product Code	10677
---------------------	-------

Reference

Guarantee	3 Years
EAN	5013588106779
Commodity Code	94054099
Country Of Origin	CN
UNSPSC Code	39111515

Technical Specification

Volts (V)	220-240
Watts (W)	5
Colour Temp (K)	3000
Dimmable?	1
Lumens (lm)	462
Life Hours	35,000
Beam Angle	60°
CRI (Ra)	80
Frequency (Hz)	50
LED Drive Current	14
Energy Consumption (kWh/1000h)	5
IP Rating	IP65

Dimensions

Height (mm)	82
Width (mm)	88
Depth (mm)	76
Length (mm)	125
Diameter (mm)	80
Downlight Cut Out (mm)	60

Packaging Information

Single Carton Height (mm)	9.5
Single Carton Width (mm)	9
Single Carton Depth (mm)	7.5
Single Carton Weight (KG)	0.5
Individual Volume	0.00064
Outer Box Qty	20
Outer Box Height (mm)	16.5
Outer Box Width (mm)	47
Outer Box Depth (mm)	20.5
Outer Box CMB	0.0159