

Fittings / Downlights

5W Firestay Slim Centre Tilt Integrated Fixed Downlight Satin - 3000K

The most cost effective integrated downlight in the BELL range, the Firestay Slim comes with a 3 year quality guarantee. Fixed and Centre Tilt options available with a choice of finishes and colour temperatures.

- Firestay Certification: 30, 60 and 90 minute solid joist ceilings, 30 minute I-Joist & Metal Web ceiling systems
- IP65 - Fixed Versions / IP44 - Tilt Version
- Cut Out Ø55-68 mm
- Part B/C/E compliant
- Dimmable

Technical Specification

Product Code	10683
--------------	-------

Reference

Guarantee	3 Years
EAN	5013588106830
Commodity Code	9405409990
Country Of Origin	CN
UNSPSC Code	39111515

Technical Specification

Volts (V)	220-240
Watts (W)	5
Colour Temp (K)	3000
Dimmable?	1
Lumens (lm)	450
Life Hours	35,000
Beam Angle	60°
CRI (Ra)	80
Frequency (Hz)	50
LED Drive Current	14
Energy Consumption (kWh/1000h)	5
IP Rating	IP20

Dimensions

Height (mm)	96
Width (mm)	89.5
Depth (mm)	90
Length (mm)	126
Diameter (mm)	81.5
Downlight Cut Out (mm)	65

Packaging Information

Single Carton Height (mm)	100
Single Carton Width (mm)	100
Single Carton Depth (mm)	85
Single Carton Weight (KG)	0.3
Individual Volume	0.00085
Inner Box Qty	10
Inner Box Height (mm)	515
Inner Box Width (mm)	210
Inner Box Depth (mm)	95
Inner Box Weight (kg)	3.15
Outer Box Qty	10
Outer Box Height (mm)	535
Outer Box Width (mm)	230
Outer Box Depth (mm)	215
Outer Box Weight (kg)	6.5