



Fittings / Downlights

16W Arial Pro Downlight IP44 - 1-10V Dim, CCT



The Arial Pro LED Downlight is a sleek looking luminaire designed to replace cumbersome CFL fittings. With a 7 year guarantee across both the IP44 & IP65 range, the Arial Pro can be installed in a variety of applications with the confidence of knowing this product will stand the test of time.

- Switchable colour temperature 3000/4000/6000K
- Ideal for home and office environments
- Equivalent up to 2x26W fluorescent
- Anti-glare
- Tool Free Plug & Play

Technical Specification

7 Years
5013588109602
1

CN

39111515

www.belllighting.co.uk

Country Of Origin

UNSPSC Code



This document is uncontrolled if printed, all information is subject to change. Generated on 4/28/2024 6:55:15 PM





Technical Specification

Watts (W)16Colour Temp (K)3000/4000/6000Dimmable?1Lumens (Im)1660Life Hours50,000Beam Angle90°CRI (Ra)85Switching Cycles25,000Frequency (Hz)50/60LED Drive Current400Energy Consumption (kWh/1000h)16IP RatingIP44Dimensions102Height (mm)102Downlight Cut Out (mm)160-170Packaging Information20Single Carton Height (mm)20Single Carton Weight (KG)0.655Individual Volume0.00504Outer Box Oty12Outer Box Width (mm)41.5Outer Box CMB0.06889	Volts (V)	220-240
Dimmable?1Lumens (Im)1660Life Hours50,000Beam Angle90°CRI (Ra)85Switching Cycles25,000Frequency (Hz)50/60LED Drive Current400Energy Consumption (kWh/1000h)16IP RatingIP44Dimensions102Height (mm)102Diameter (mm)160-170Packaging Information12.6Single Carton Height (mm)20Single Carton Width (mm)20Single Carton Weight (KG)0.655Individual Volume0.00504Outer Box Height (mm)41.5Outer Box Width (mm)41.5	Watts (W)	16
Lumens (Im)1660Life Hours50,000Beam Angle90°CRI (Ra)85Switching Cycles25,000Frequency (Hz)50/60LED Drive Current400Energy Consumption (kWh/1000h)16IP RatingIP44Dimensions102Height (mm)102Downlight Cut Out (mm)160-170Packaging Information12.6Single Carton Height (mm)20Single Carton Depth (mm)20Single Carton Weight (KG)0.65Individual Volume0.00504Outer Box Ady41.5Outer Box Width (mm)41.5Outer Box Depth (mm)41.5	Colour Temp (K)	3000/4000/6000
Life Hours50,000Beam Angle90°CRI (Ra)85Switching Cycles25,000Frequency (Hz)50/60LED Drive Current400Energy Consumption (kWh/1000h)16IP RatingIP44Dimensions102Height (mm)102Downlight Cut Out (mm)160-170Packaging Information12.6Single Carton Height (mm)20Single Carton Depth (mm)20Single Carton Weight (KG)0.65Individual Volume0.00504Outer Box Qty12Outer Box Width (mm)41.5Outer Box Width (mm)41.5	Dimmable?	1
Beam Angle90°CRI (Ra)85Switching Cycles25,000Frequency (Hz)50/60LED Drive Current400Energy Consumption (kWh/1000h)16IP RatingIP44Dimensions102Height (mm)102Diameter (mm)190Downlight Cut Out (mm)160-170Packaging Information20Single Carton Height (mm)20Single Carton Weight (KG)0.65Individual Volume0.00504Outer Box Qty12Outer Box Width (mm)41.5Outer Box Depth (mm)41.5	Lumens (lm)	1660
CRI (Ra)85Switching Cycles25,000Frequency (Hz)50/60LED Drive Current400Energy Consumption (kWh/1000h)16IP RatingIP44Dimensions102Diameter (mm)100Downlight Cut Out (mm)160-170Packaging Information12.6Single Carton Height (mm)20Single Carton Weight (KG)0.65Individual Volume0.00504Outer Box Qty12Outer Box Width (mm)41.5Outer Box Depth (mm)41.5	Life Hours	50,000
Switching Cycles25,000Frequency (Hz)50/60LED Drive Current400Energy Consumption (kWh/1000h)16IP RatingIP44Dimensions102Height (mm)102Diameter (mm)190Downlight Cut Out (mm)160-170Packaging Information20Single Carton Height (mm)20Single Carton Depth (mm)20Single Carton Weight (KG)0.65Individual Volume0.00504Outer Box Qty12Outer Box Width (mm)41.5Outer Box Depth (mm)41.5	Beam Angle	90°
Frequency (Hz)50/60LED Drive Current400Energy Consumption (kWh/1000h)16IP RatingIP44DimensionsIP44Dimensions102Diameter (mm)190Downlight Cut Out (mm)160-170Packaging Information20Single Carton Height (mm)20Single Carton Width (mm)20Single Carton Width (mm)20Outer Box Qty12Outer Box Width (mm)41.5Outer Box Width (mm)41.5	CRI (Ra)	85
LED Drive Current400Energy Consumption (kWh/1000h)16IP RatingIP44DimensionsIP44Dimensions102Height (mm)102Diameter (mm)190Downlight Cut Out (mm)160-170Packaging Information20Single Carton Height (mm)20Single Carton Depth (mm)20Single Carton Width (mm)20Outer Box Qty12Outer Box Meight (mm)41.5Outer Box Width (mm)41.5	Switching Cycles	25,000
Energy Consumption (kWh/1000h)16IP RatingIP44DimensionsIP44Dimensions102Height (mm)102Diameter (mm)190Downlight Cut Out (mm)160-170Packaging Information20Single Carton Height (mm)20Single Carton Width (mm)20Single Carton Depth (mm)20Single Carton Weight (KG)0.65Individual Volume0.00504Outer Box Qty12Outer Box Width (mm)41.5Outer Box Depth (mm)41.5	Frequency (Hz)	50/60
IP RatingIP44Dimensions102Height (mm)102Diameter (mm)190Downlight Cut Out (mm)160-170Packaging Information12.6Single Carton Height (mm)20Single Carton Width (mm)20Single Carton Depth (mm)20Single Carton Weight (KG)0.65Individual Volume0.00504Outer Box Qty12Outer Box Height (mm)41.5Outer Box Depth (mm)41.5	LED Drive Current	400
DimensionsHeight (mm)102Diameter (mm)190Downlight Cut Out (mm)160-170Packaging Information12.6Single Carton Height (mm)12.6Single Carton Width (mm)20Single Carton Depth (mm)20Single Carton Weight (KG)0.655Individual Volume0.00504Outer Box Atty12Outer Box Height (mm)41.5Outer Box Depth (mm)41.5	Energy Consumption (kWh/1000h)	16
Height (mm)102Diameter (mm)190Downlight Cut Out (mm)160-170Packaging Information12.6Single Carton Height (mm)20Single Carton Width (mm)20Single Carton Depth (mm)20Single Carton Weight (KG)0.65Individual Volume0.00504Outer Box Qty12Outer Box Height (mm)40Outer Box Width (mm)41.5Outer Box Depth (mm)41.5	IP Rating	IP44
Diameter (mm)190Downlight Cut Out (mm)160-170Packaging Information12.6Single Carton Height (mm)12.6Single Carton Width (mm)20Single Carton Depth (mm)20Single Carton Weight (KG)0.65Individual Volume0.00504Outer Box Qty12Outer Box Height (mm)40Outer Box Width (mm)41.5Outer Box Depth (mm)41.5	Dimensions	
Downlight Cut Out (mm)160-170Packaging Information12.6Single Carton Height (mm)12.6Single Carton Width (mm)20Single Carton Depth (mm)20Single Carton Weight (KG)0.65Individual Volume0.00504Outer Box Qty12Outer Box Height (mm)40Outer Box Width (mm)41.5Outer Box Depth (mm)41.5	Height (mm)	102
Packaging InformationSingle Carton Height (mm)12.6Single Carton Width (mm)20Single Carton Depth (mm)20Single Carton Weight (KG)0.65Individual Volume0.00504Outer Box Qty12Outer Box Height (mm)40Outer Box Width (mm)41.5Outer Box Depth (mm)41.5	Diameter (mm)	190
Single Carton Height (mm)12.6Single Carton Width (mm)20Single Carton Depth (mm)20Single Carton Weight (KG)0.65Individual Volume0.00504Outer Box Qty12Outer Box Height (mm)40Outer Box Width (mm)41.5Outer Box Depth (mm)41.5	Downlight Cut Out (mm)	160-170
Single Carton Width (mm)20Single Carton Depth (mm)20Single Carton Weight (KG)0.65Individual Volume0.00504Outer Box Qty12Outer Box Height (mm)40Outer Box Width (mm)41.5Outer Box Depth (mm)41.5	Packaging Information	
Single Carton Depth (mm)20Single Carton Weight (KG)0.65Individual Volume0.00504Outer Box Qty12Outer Box Height (mm)40Outer Box Width (mm)41.5Outer Box Depth (mm)41.5	Single Carton Height (mm)	12.6
Single Carton Weight (KG)0.65Individual Volume0.00504Outer Box Qty12Outer Box Height (mm)40Outer Box Width (mm)41.5Outer Box Depth (mm)41.5	Single Carton Width (mm)	20
Individual Volume0.00504Outer Box Qty12Outer Box Height (mm)40Outer Box Width (mm)41.5Outer Box Depth (mm)41.5	Single Carton Depth (mm)	20
Outer Box Qty12Outer Box Height (mm)40Outer Box Width (mm)41.5Outer Box Depth (mm)41.5	Single Carton Weight (KG)	0.65
Outer Box Height (mm)40Outer Box Width (mm)41.5Outer Box Depth (mm)41.5	Individual Volume	0.00504
Outer Box Width (mm)41.5Outer Box Depth (mm)41.5	Outer Box Qty	12
Outer Box Depth (mm) 41.5	Outer Box Height (mm)	40
	Outer Box Width (mm)	41.5
Outer Box CMB 0.06889	Outer Box Depth (mm)	41.5
	Outer Box CMB	0.06889

www.belllighting.co.uk



This document is uncontrolled if printed, all information is subject to change. Generated on 4/28/2024 6:55:15 PM