



Fittings / Downlights

20W Arial Pro Downlight IP65 - Emergency (1Y), CCT

The Arial Pro LED Downlight is a sleek looking luminaire designed to replace cumbersome CFL fittings. With a 7 year guarantee across both the IP44 & IP65 range, the Arial Pro can be installed in a variety of applications with the confidence of knowing this product will stand the test of time.

- Switchable colour temperature 3000/4000/6000K
- Ideal for home and office environments
- Equivalent up to 2x26W fluorescent
- Anti-glare

Product Code

• Tool Free - Plug & Play

Technical Specification

| Reference | |
|-------------------|---------------|
| Guarantee | 7 Years |
| EAN | 5013588109671 |
| Commodity Code | 9405409990 |
| Country Of Origin | CN |
| UNSPSC Code | 39111515 |

10967









Technical Specification

| Volts (V) | 220-240 |
|--------------------------------|----------------|
| Watts (W) | 20 |
| Colour Temp (K) | 3000/4000/6000 |
| Dimmable? | 0 |
| Lumens (lm) | 2250 |
| Life Hours | 50,000 |
| Beam Angle | 90° |
| CRI (Ra) | 85 |
| Switching Cycles | 25,000 |
| Frequency (Hz) | 50/60 |
| LED Drive Current | 500 |
| Energy Consumption (kWh/1000h) | 20 |
| IP Rating | IP65 |
| Dimensions | |
| Height (mm) | 117 |
| Diameter (mm) | 240 |
| Downlight Cut Out (mm) | 200-210 |
| Packaging Information | |
| Single Carton Height (mm) | 143 |
| Single Carton Width (mm) | 250 |
| Single Carton Depth (mm) | 250 |
| Single Carton Weight (KG) | 2.35 |
| Individual Volume | 0.00894 |
| Out Development | |
| Outer Box Height (mm) | 450 |
| Outer Box Width (mm) | 450 515 |



