Fittings / LED Floodlights

100W Skyline Slim+ Asymmetric LED Floodlight - 4000K

The Skyline Slim+ LED Floodlight is suitable for a wide range of applications. Available in a vast range of wattages, this low energy floodlight is ideal for any lighting project, big or small.

- Marine Grade Aluminium body
- Fully encapsulated IP65 TUV certified driver
- PIR Over-ride function
- Average 8M detection range for PIR Floods
- Separately tested IP65 PIR

Technical Specification

Product Code	10977

Reference

Guarantee	5 Years
EAN	5013588109770
Commodity Code	9405423990
Country Of Origin	CN
UNSPSC Code	39111626

Technical Specification

Volts (V)	240
Watts (W)	100
Colour Temp (K)	4000
Dimmable?	0
Lumens (lm)	11000
Life Hours	50,000
CRI (Ra)	80
Switching Cycles	25,000
Frequency (Hz)	50/60
LED Drive Current	930
Energy Consumption (kWh/1000h)	100
IP Rating	IP65

Dimensions

Height (mm)	315
Width (mm)	277
Depth (mm)	60

Packaging Information

Single Carton Height (mm)	280
Single Carton Width (mm)	70
Single Carton Depth (mm)	323
Single Carton Weight (KG)	3.28437
Individual Volume	0.00633
Outer Box Qty	50
Outer Box Height (mm)	292
Outer Box Width (mm)	284
Outer Box Depth (mm)	329
Outer Box Weight (kg)	13.6759

E: sales@belllighting.co.uk
T: 01924 893380

www.belllighting.co.uk

This document is uncontrolled if printed, all information is subject to change. Generated on 5/2/2024 9:11:55 PM