



Fittings / LED Floodlights

20W Skyline Slim+ LED Floodlight - 4000K

The Skyline Slim+ LED Floodlight is suitable for a wide range of applications. Available in a vast range of wattages, this low energy floodlight is ideal for any lighting project, big or small.

10981

• Marine Grade Aluminium body

Product Code

• Fully encapsulated IP65 TUV certified driver

Technical Specification

Reference	
Guarantee	5 Years
EAN	5013588109817
Commodity Code	9405423990
Country Of Origin	CN
UNSPSC Code	39111626
Technical Specification	
Volts (V)	240
Watts (W)	20
Colour Temp (K)	4000
Dimmable?	0
Lumens (lm)	2400
Life Hours	50,000
Beam Angle	110°
CRI (Ra)	80
Switching Cycles	25,000
Frequency (Hz)	50/60
LED Drive Current	230
Energy Consumption (kWh/1000h)	20
IP Rating	IP65

E: sales@belllighting.co.uk T: 01924 893380







Dimensions

Height (mm)	142
Width (mm)	120
Depth (mm)	33
Packaging Information	
Single Carton Height (mm)	14.2
Single Carton Width (mm)	12
Single Carton Depth (mm)	5.1
Individual Volume	0.00087
Outer Box Qty	12
Outer Box Height (mm)	17.2
Outer Box Width (mm)	33.5
Outer Box Depth (mm)	25.8



