

Fittings / LED Panels

36W Arial Backlit High Output UGR <19 LED Panel 1200x300mm, 4000K



The Arial Plus is our leading panel when it comes to performance. With a high lumen output of over 120 lumens per watt, this panel is ideal for areas that require high lux levels. The Arial Plus can be installed in areas where TPa rated lighting products are essential, such as emergency exit routes including stairways and corridors.

- High efficiency
- TPa
- Uniform light distribution
- Professional LED Panel
- Anti-twist frame

Technical Specification

Product Code	11010
--------------	-------

Reference

Guarantee	7 Years
EAN	5013588110103
Commodity Code	9405409990
Country Of Origin	CN
UNSPSC Code	39111544

Technical Specification

Volts (V)	220-240
Watts (W)	36
Colour Temp (K)	4000
Dimmable?	0
Lumens (lm)	4320
Life Hours	50,000
CRI (Ra)	>80
Switching Cycles	25,000
Frequency (Hz)	50/60
IP Rating	IP20

Dimensions

Height (mm)	1,195
Width (mm)	295
Depth (mm)	32

Packaging Information

Single Carton Height (mm)	655
Single Carton Width (mm)	52
Single Carton Depth (mm)	1248
Single Carton Weight (KG)	2.42
Individual Volume	0.02304
Inner Box Qty	1
Outer Box Qty	5
Outer Box Height (mm)	375
Outer Box Width (mm)	290
Outer Box Depth (mm)	1260
Outer Box CMB	0.13703