



Fittings / LED Panels

58W Arial Backlit High Output UGR <19 LED Panel 1200x600mm, 4000K

The Arial Plus is our leading panel when it comes to performance. With a high lumen output of over 120 lumens per watt, this panel is ideal for areas that require high lux levels. The Arial Plus can be installed in areas where TPa rated lighting products are essential, such as emergency exit routes including stairways and corridors.

- High efficiency
- TPa
- Uniform light distribution
- Professional LED Panel
- Anti-twist frame

Technical Specification

Product Code	11020
Reference	
Guarantee	7 Years
EAN	5013588110202
Commodity Code	9405409990
Country Of Origin	CN
UNSPSC Code	39111544

www.belllighting.co.uk



This document is uncontrolled if printed, all information is subject to change. Generated on 5/3/2024 9:12:47 PM





Technical Specification

Volts (V)	220-240
Watts (W)	58
Colour Temp (K)	4000
Dimmable?	0
Lumens (lm)	6960
Life Hours	50,000
CRI (Ra)	>80
Switching Cycles	25,000
Frequency (Hz)	50/60
IP Rating	IP20
Dimensions	
Height (mm)	1,195
Width (mm)	595
Depth (mm)	32
Packaging Information	
Single Carton Height (mm)	655
Single Carton Width (mm)	52
Single Carton Depth (mm)	1248
Single Carton Weight (KG)	4.5
Individual Volume	0.04251
Inner Box Qty	1
Outer Box Qty	4
Outer Box Height (mm)	675
Outer Box Width (mm)	235
Outer Box Depth (mm)	1260

E: sales@belllighting.co.uk **T:** 01924 893380

www.belllighting.co.uk



This document is uncontrolled if printed, all information is subject to change. Generated on 5/3/2024 9:12:47 PM