



Fittings / LED Panels

58W Arial Backlit High Output UGR <19 LED Panel 1200x600mm, Emergency Dali, 4000K



The Arial Plus is our leading panel when it comes to performance. With a high lumen output of over 120 lumens per watt, this panel is ideal for areas that require high lux levels. The Arial Plus can be installed in areas where TPa rated lighting products are essential, such as emergency exit routes including stairways and corridors.

- High efficiency
- TPa
- Uniform light distribution
- Professional LED Panel
- Anti-twist frame

Technical Specification

Product Code	11025
Reference	
Guarantee	7 Years
EAN	5013588110257
Commodity Code	9405409990
Country Of Origin	CN
UNSPSC Code	39111544

www.belllighting.co.uk



This document is uncontrolled if printed, all information is subject to change. Generated on 5/2/2024 9:36:04 AM





Technical Specification

Volts (V)	220-240
Watts (W)	58
Colour Temp (K)	4000
Dimmable?	1
Lumens (lm)	6960
Life Hours	50,000
CRI (Ra)	>80
Switching Cycles	25,000
Frequency (Hz)	50/60
IP Rating	IP20
Dimensions	
Height (mm)	1,195
Width (mm)	595
Depth (mm)	32
Depth (mm) Packaging Information	32
	32 655
Packaging Information	
Packaging Information Single Carton Height (mm)	655
Packaging Information Single Carton Height (mm) Single Carton Width (mm)	655 1248
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm)	655 1248 52
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (KG)	655 1248 52 6
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (KG) Individual Volume	655 1248 52 6 0.04251
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (KG) Individual Volume Inner Box Qty	655 1248 52 6 0.04251 1
Packaging InformationSingle Carton Height (mm)Single Carton Width (mm)Single Carton Depth (mm)Single Carton Weight (KG)Individual VolumeInner Box QtyOuter Box Qty	655 1248 52 6 0.04251 1 50
Packaging InformationSingle Carton Height (mm)Single Carton Width (mm)Single Carton Depth (mm)Single Carton Weight (KG)Individual VolumeInner Box QtyOuter Box QtyOuter Box Height (mm)	655 1248 52 6 0.04251 1 50 675
Packaging InformationSingle Carton Height (mm)Single Carton Width (mm)Single Carton Depth (mm)Single Carton Weight (KG)Individual VolumeInner Box QtyOuter Box QtyOuter Box Height (mm)Outer Box Width (mm)	655 1248 52 6 0.04251 1 50 675 1260

www.belllighting.co.uk



This document is uncontrolled if printed, all information is subject to change. Generated on 5/2/2024 9:36:04 AM