



### Fittings / LED Warehouse Lighting


# Illumina Linear 200W LED UGR Symmetric High Bay in Emergency - 4000K



The Illumina Linear offers a sleek design coupled with high performance. Perfect for high ceiling warehouses, industrial facilities, exhibition centres, shopping malls, sports halls & stadiums.

- TUV Isolated Driver
- Suitable for High Bay and Low Bay applications 4-12m
- Plug-in PIR and Microwave sensors
- Sensor parameters set by remote control
- Specially designed for low glare sports and warehouse lighting

### **Technical Specification**



Product Code	11321

#### Reference

Guarantee	7 Years
EAN	5013588113210
Commodity Code	9405423990
Country of Origin	CN
UNSPSC Code	39111546

www.belllighting.co.uk







## **Technical Specification**

Watts (W)200Colour Temp (K)4000Dimmable?0Lumens (Im)28000Life Hours50,000CRI (ra)85Switching Cycles100,000Frequency (Hz)50/60LED Drive Current124Energy Consumption (kWh/1000h)200IP RatingIP65Dimensions113	
Dimmable?0Lumens (Im)28000Life Hours50,000CRI (ra)85Switching Cycles100,000Frequency (Hz)50/60LED Drive Current124Energy Consumption (kWh/1000h)200IP RatingIP65Dimensions	
Lumens (Im)28000Life Hours50,000CRI (ra)85Switching Cycles100,000Frequency (Hz)50/60LED Drive Current124Energy Consumption (kWh/1000h)200IP RatingIP65Dimensions	
Life Hours50,000CRI (ra)85Switching Cycles100,000Frequency (Hz)50/60LED Drive Current124Energy Consumption (kWh/1000h)200IP RatingIP65Dimensions	
CRI (ra)85Switching Cycles100,000Frequency (Hz)50/60LED Drive Current124Energy Consumption (kWh/1000h)200IP RatingIP65Dimensions	
Switching Cycles100,000Frequency (Hz)50/60LED Drive Current124Energy Consumption (kWh/1000h)200IP RatingIP65Dimensions	
Frequency (Hz)50/60LED Drive Current124Energy Consumption (kWh/1000h)200IP RatingIP65Dimensions	
LED Drive Current124Energy Consumption (kWh/1000h)200IP RatingIP65Dimensions	
Energy Consumption (kWh/1000h)200IP RatingIP65Dimensions	
IP Rating IP65 Dimensions	
Dimensions	
Height (mm) 113	
Width (mm) 118	
Length (mm) 1,293	
Packaging Information	
Single Carton Height (mm) 1350	
Single Carton Width (mm) 130	
Single Carton Depth (mm)155	
Single Carton Weight (kg)6.5	
Individual Volume 0.0272	
Outer Box Qty 1	

www.belllighting.co.uk

