

Fittings / LED Panels


36W Arial Plus Backlit LED Panel - 25mm 600x600mm, 4000K, UGR<19, White, Dali Dim



The Arial Plus is our leading panel when it comes to performance. With a high lumen output of over 120 lumens per watt, this panel is ideal for areas that require high lux levels. The Arial Plus can be installed in areas where TPa rated lighting products are essential, such as emergency exit routes including stairways and corridors.

- High efficiency
- TPa
- Uniform light distribution
- Professional LED Panel
- Anti-twist frame

Technical Specification



Product Code	11633
--------------	-------

Reference

Guarantee	7 Years
EAN	5013588116334
Commodity Code	9405409990
Country of Origin	CN
UNSPSC Code	39111544

Technical Specification

Volts (V)	220-240
Watts (W)	36
Colour Temp (K)	4000
Dimmable?	0
Lumens (lm)	3841
Life Hours	50,000
CRI (ra)	>80
Switching Cycles	25,000
Frequency (Hz)	50/60
IP Rating	IP20

Dimensions

Height (mm)	595
Width (mm)	595
Depth (mm)	25

Packaging Information

Single Carton Height (mm)	655
Single Carton Width (mm)	52
Single Carton Depth (mm)	648
Single Carton Weight (kg)	2.2
Individual Volume	0.02207
Inner Box Qty	1
Outer Box Height (mm)	675
Outer Box Width (mm)	290
Outer Box Depth (mm)	660