



Fittings / LED Panels


36W Arial Plus Backlit LED Panel - 25mm 600x600mm, 4000K, UGR<19, White, 0-10V Dim



The Arial Plus is our leading panel when it comes to performance. With a high lumen output of over 120 lumens per watt, this panel is ideal for areas that require high lux levels. The Arial Plus can be installed in areas where TPa rated lighting products are essential, such as emergency exit routes including stairways and corridors.

- High efficiency
- TPa
- Uniform light distribution
- Professional LED Panel
- Anti-twist frame

Technical Specification



ReferenceGuarantee7 YearsEAN5013588116341	Product Code	11634
Guarantee 7 Years		
	Reference	
EAN 5013588116341	Guarantee	7 Years
	EAN	5013588116341
Commodity Code 9405409990	Commodity Code	9405409990
Country of Origin CN	Country of Origin	CN
UNSPSC Code 39111544	UNSPSC Code	39111544

E: sales@belllighting.co.uk **T:** 01924 893380

www.belllighting.co.uk



This document is uncontrolled if printed, all information is subject to change. Generated on 5/15/2024 4:49:53 AM





Technical Specification

Volts (V)	220-240
Watts (W)	36
Colour Temp (K)	4000
Dimmable?	0
Lumens (lm)	3841
Life Hours	50,000
CRI (ra)	>80
Switching Cycles	25,000
Frequency (Hz)	50/60
IP Rating	IP20
Dimensions	
Height (mm)	595
Width (mm)	595
Depth (mm)	25
Packaging Information	
Single Carton Height (mm)	655
Single Carton Width (mm)	52
Single Carton Depth (mm)	648
Single Carton Weight (kg)	2.2
Individual Volume	0.02207
Inner Box Qty	1
Outer Box Height (mm)	675
Outer Box Width (mm)	290
Outer Box Depth (mm)	660
Outer Box Depth (mm)	660

E: sales@belllighting.co.uk **T:** 01924 893380

www.belllighting.co.uk



This document is uncontrolled if printed, all information is subject to change. Generated on 5/15/2024 4:49:53 AM