



Fittings / LED Panels


25W Arial Plus Backlit LED Panel - 25mm 600x600mm, 4000K, UGR<19, White



The Arial Plus is our leading panel when it comes to performance. With a high lumen output of over 120 lumens per watt, this panel is ideal for areas that require high lux levels. The Arial Plus can be installed in areas where TPa rated lighting products are essential, such as emergency exit routes including stairways and corridors.

- High efficiency
- TPa
- Uniform light distribution
- Professional LED Panel
- Anti-twist frame

Technical Specification



Product Code	11660
Reference	
Guarantee	7 Years
EAN	5013588116600
Commodity Code	9405409990
Country of Origin	CN
UNSPSC Code	39111544

E: sales@belllighting.co.uk **T:** 01924 893380

www.belllighting.co.uk



This document is uncontrolled if printed, all information is subject to change. Generated on 5/14/2024 4:46:15 AM





Technical Specification

Volts (V)	220-240
Watts (W)	25
Colour Temp (K)	4000
Dimmable?	0
Lumens (lm)	3250
Life Hours	50,000
CRI (ra)	>80
Switching Cycles	25,000
Frequency (Hz)	50/60
IP Rating	IP20
Dimensions	
Height (mm)	595
Width (mm)	595
Depth (mm)	25
Packaging Information	
Single Carton Height (mm)	620
Single Carton Width (mm)	35
Single Carton Depth (mm)	672
Single Carton Weight (kg)	2.46
Individual Volume	0.01458
Inner Box Qty	1
Inner Box Height (mm)	620
Inner Box Width (mm)	35
Inner Box Depth (mm)	672
Inner Box Weight (kg)	2.46
Outer Box Height (mm)	635
Outer Box Width (mm)	240
Outer Box Depth (mm)	685
Outer Box Weight (kg)	14.78

www.belllighting.co.uk



This document is uncontrolled if printed, all information is subject to change. Generated on 5/14/2024 4:46:15 AM