

Fittings / LED Panels

Arial Plus Backlit 58W LED UGR<19 1200x600 White Panel in Emergency (1Y) - 25mm Deep - 4000K



The Arial Plus is our leading panel when it comes to performance. With a high lumen output of over 120 lumens per watt, this panel is ideal for areas that require high lux levels. The Arial Plus can be installed in areas where TPa rated lighting products are essential, such as emergency exit routes including stairways and corridors.

- High efficiency
- TPa
- Uniform light distribution
- Professional LED Panel
- Anti-twist frame

Technical Specification

Product Code	11689
--------------	-------

Reference

Guarantee	7 Years
EAN	5013588116891
Commodity Code	9405409990
Country of Origin	CN
UNSPSC Code	39111544

Technical Specification

Volts (V)	220-240
Watts (W)	58
Colour Temp (K)	4000
Dimmable?	0
Lumens (lm)	6960
Life Hours	50,000
CRI (ra)	>80
Switching Cycles	25,000
Frequency (Hz)	50/60
IP Rating	IP20

Dimensions

Height (mm)	1,195
Width (mm)	595
Depth (mm)	25

Packaging Information

Single Carton Height (mm)	655
Single Carton Width (mm)	52
Single Carton Depth (mm)	1248
Single Carton Weight (kg)	6
Individual Volume	0.04251
Inner Box Qty	1
Outer Box Height (mm)	675
Outer Box Width (mm)	235
Outer Box Depth (mm)	1260