



## Lamps / LED

4W LED Filament Clear Round Dimmable - BC, 4000K (Upgraded Product – Order New Code: 60746)

> The LED Filament Range combines LED technology with the elegance of Incandescent Lamps. Creating a welcoming atmosphere with a retro feel, our LED Filament Range offers smooth dimming on rotary and digital dimming systems. The Filament Round is ideal for all bedside decorative lighting along with all other similar applications.

- LED Technology with the elegance of Incandescent Lamps
- Creates a welcoming atmosphere with retro feel
- Argon gas filled to improve life
- Smooth dimming on rotary and digital dimming systems
- Full glass envelope (exc SBC & SES)

## **Technical Specification**

Product Code	60123
Reference	
Guarantee	3 Years
EAN	5013588601236
Commodity Code	85395000
Country Of Origin	CN
UNSPSC Code	39101628

www.belllighting.co.uk



This document is uncontrolled if printed, all information is subject to change. Generated on 5/3/2024 11:12:37 PM





## **Technical Specification**

Watts (W)4CapBC/B22Colour Temp (K)4000Dimmable?1Lumens (Im)470Life Hours15,000Beam Angle300°Energy RatingECRI (Ra)85Switching Cycles8,000Frequency (Hz)50/60Energy Consumption (kWh/1000h)4Dimensions78Height (mm)78Diameter (mm)45Packaging Information90
Colour Temp (K)4000Dimmable?1Lumens (Im)470Life Hours15,000Beam Angle300°Energy RatingECRI (Ra)85Switching Cycles8,000Frequency (Hz)50/60Energy Consumption (kWh/1000h)4Dimensions78Height (mm)78Diameter (mm)45
Dimmable?1Lumens (Im)470Life Hours15,000Beam Angle300°Energy RatingECRI (Ra)85Switching Cycles8,000Frequency (Hz)50/60Energy Consumption (kWh/1000h)4Dimensions78Height (mm)78Diameter (mm)45
Lumens (Im)470Life Hours15,000Beam Angle300°Energy RatingECRI (Ra)85Switching Cycles8,000Frequency (Hz)50/60Energy Consumption (kWh/1000h)4Dimensions78Height (mm)78Diameter (mm)45
Life Hours15,000Beam Angle300°Energy RatingECRI (Ra)85Switching Cycles8,000Frequency (Hz)50/60Energy Consumption (kWh/1000h)4Dimensions78Height (mm)78Diameter (mm)45
Beam Angle300°Energy RatingECRI (Ra)85Switching Cycles8,000Frequency (Hz)50/60Energy Consumption (kWh/1000h)4Dimensions78Height (mm)78Diameter (mm)45Packaging Information
Energy RatingECRI (Ra)85Switching Cycles8,000Frequency (Hz)50/60Energy Consumption (kWh/1000h)4Dimensions78Height (mm)78Diameter (mm)45Packaging Information
CRI (Ra)85Switching Cycles8,000Frequency (Hz)50/60Energy Consumption (kWh/1000h)4Dimensions78Height (mm)78Diameter (mm)45Packaging Information
Switching Cycles8,000Frequency (Hz)50/60Energy Consumption (kWh/1000h)4Dimensions78Height (mm)78Diameter (mm)45Packaging Information
Frequency (Hz)50/60Energy Consumption (kWh/1000h)4Dimensions78Height (mm)78Diameter (mm)45Packaging Information
Energy Consumption (kWh/1000h)4DimensionsHeight (mm)78Diameter (mm)45Packaging Information
Dimensions   Height (mm)   78   Diameter (mm)   45   Packaging Information
Height (mm)78Diameter (mm)45Packaging Information
Diameter (mm) 45   Packaging Information
Packaging Information
Single Carton Height (mm) 90
Single Carton Width (mm) 50
Single Carton Depth (mm) 50
Single Carton Weight (KG) 0.04
Individual Volume 0.00023
Inner Box Qty 10
Inner Box Height (mm) 100
Inner Box Width (mm) 270
Inner Box Depth (mm) 110
Inner Box Weight (kg) 0.41
Outer Box Qty 100
Outer Box Qty100Outer Box Height (mm)220

www.belllighting.co.uk



This document is uncontrolled if printed, all information is subject to change. Generated on 5/3/2024 11:12:37 PM