Cable handling

TITLE:
Drum-Roll Cable Routing

CODE:
SFX/ACC-DRUM-FLEXIPASS-1

DESCRIPTION:
Drum-Roll Flexipass

SUPPLIED AS:
FLEXIPASS

FLAME-FLEX® Drum-R☉ll LUCKINS™ epim ELECTRICAL DISTRIBUTORS' ASSOCIATION BASEC KNX MEMBER cai CPR UKCA

Product Specification

Technical Data

Weight (kg)	0.85
Length (m)	0.365
Width (m)	0.17
Height (m)	0.08
Packaging	Carton
Max Cable Diameter	38mm
Max Clamping Width	48mm

FLAME-FLEX®   Drum-Roll   LUCKINS™   epim   EDA ELECTRICAL DISTRIBUTORS' ASSOCIATION   BASEC   KNX MEMBER   cai   CPR   UK CA

Securi-Flex®

MORE INFORMATION:

TECHNICAL DATA

A) Max. cable Ø	38 mm
B) Max. clamping width	48 mm
Width (widest point)	65 mm
C) Length	331 – 379 mm
D) Height	148 mm
Own weight	850 g

ORDER NO.

FLEXIPASS	ACC-DRUM-FLEXIPASS-3
(Set = 3 pcs.)	
incl. carrying bag	
FLEXIPASS (single)	SFX/ACC-DRUM-FLEXIPASS-1

FLAME-FLEX® Drum-Roll LUCKINS™ epim ELECTRICAL DISTRIBUTORS' ASSOCIATION BASEC KNX MEMBER cai CPR UKCA