

NETWORK CABLE



TITLE:

Cat5e 4pr FTP Fire Resistant LSZH

CODE:

SFX/C5-FTP-FIRE-LSZH-RED-1


DESCRIPTION:

1m (per metre) Category 5e, 4pr FTP Fire Resistant Red LSZH

SUPPLIED AS:

Per 1m Lengths

- Capable of 100mbps transfer speed or 100mhz frequency at a maximum distance of 90 meters
- Screened for use where RF or Power equipment may produce electromagnetic interferance. This is also a security measure should eavesdropping be apparent.
- Low smoke zero halogen plastic is good for use inside public buildings and spaces as will not emit toxic gases if the cable catches fire
- Solid core is the most cost effective and commonly used type of cat5e cable































NETWORK CABLE



Product Specification



Cable Construction

CPR	LPCB
Conductor	Bare Copper
Conductor Diameter (mm)	0.625 ±0.01
Overall Diameter (mm)	10.00 ±0.20

Insulation

Insulation	HDPE
Insulation Colour	Clear (x8)
Insulation Thickness (mm)	0.1
Outer Insulation	Silicon Rubber
Outer Insulation Diameter (mm)	1.60 ±0.10
Outer Insulation Thickness (mm)	0.15

Outer/Jacket Specification

Jacket LSZH Overall Colour Red Overall Diameter (mm) 10.00 ±0.20 Jacket Colour Red RAL 3017	Outer Insulation	Silicon Rubber
Overall Diameter (mm) 10.00 ±0.20	Jacket	LSZH
· ·	Overall Colour	Red
Jacket Colour Red RAL 3017	Overall Diameter (mm)	10.00 ±0.20
	Jacket Colour	Red RAL 3017
Jacket Thickness (mm) 1.35 ±0.20	Jacket Thickness (mm)	1.35 ±0.20

Electrical Characteristics

Max Conductor DC resistance @ 20°C	<70.7O/km
Rated Temperature (°C)	-40°C to 70°C

























MORE INFORMATION:

Sorry, no more information is available for this product

















