

**TITLE:**

Cat6a 4pr U/FTP

CODE:


SFX/C6A-UFTP-LSZH-D-PUR-1000

DESCRIPTION:

1000m Category 6A, 4pr U/FTP Purple LSZH

SUPPLIED AS:

Reel of 1000m



enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23



Product Specification

Cable Construction

CPR	Dca -s1 -a1 -d2
Conductor	Bare Copper
Conductor Diameter (mm)	0.565 ±0.005
Overall Diameter (mm)	6.80 ±0.50

Insulation

Insulation	PE
Insulation Colour	Blue/White/Blue;Orange/White/Orange;Green/White/Green;Brown/White/Brown
Insulation Thickness (mm)	0.36

Outer/Jacket Specification

Jacket	LSZH
Overall Colour	Purple
Overall Diameter (mm)	6.80 ±0.50
Jacket Colour	Purple RAL 4005
Jacket Thickness (mm)	0.50 ±0.05
Nylon Rip-Cord	White 210D

Electrical Characteristics

Max Conductor DC resistance @ 20°C	<93.80/km
Rated Temperature (°C)	-40°C to 70°C



enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23



NETWORK CABLE



MORE INFORMATION:

Sorry, no more information is available for this product

Network cable



enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23

TERMS AND CONDITIONS APPLY - WHILE EVERY EFFORT HAS BEEN MADE TO ENSURE THE ACCURACY AND COMPLETENESS OF THE INFORMATION, NO GUARANTEE IS GIVEN NOR RESPONSIBILITY TAKEN FOR ERRORS OR OMISSIONS IN THIS DATA SHEET.

FLAME-FLEX[®] Drum-Roll LUCKINS[®]

