



DEFENCE STANDARD CABLE



Defence standard cable

TITLE:

Defence 7-2 Unscreened LSZH

CODE:

SFX/DS-7-2-2A-LSZH-BLK-1



DESCRIPTION:

1m (per metre) Def Standard 7 x 0.2mm 2
Core Unscreened Black UV LSZH

SUPPLIED AS:

Per 1m Lengths

- Originally designed for military use, these cables are now widely used in many other industries and applications
- A robust, compact cable with high working voltage range
- Low smoke zero halogen plastic is good for use inside public buildings and spaces as will not emit toxic gases if the cable catches fire
- These cables should not be used for mains connections
- Improved performance and protection against fire
- Uses include security, telemetry, data processing, process control, instrumentation, control equipment and aviation



enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23



Product Specification

25-YEAR WARRANTY



Cable Construction

Cable Construction	2 Cores
CPR	Eca
Conductor	Tinned Copper
Conductor Diameter (mm)	0.19 ±0.008 x 7(0.2mm²)
Overall Diameter (mm)	3.50 ±0.20

Insulation

Insulation	LSZH
Insulation Colour	Red, Blue
Insulation Thickness (mm)	0.3

Outer/Jacket Specification

Jacket	UV LSZH
Overall Colour	Black
Overall Diameter (mm)	3.50 ±0.20
Jacket Colour	Black RAL 9005
Jacket Thickness (mm)	0.55
Nylon Rip-Cord	210D

Electrical Characteristics

Max Conductor DC resistance @ 20°C	<390/km
Rated Temperature (°C)	-40°C to 70°C
Rated Voltage (V)	600V

enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23



MORE INFORMATION:

EURO CLASS (ca:cable)		CLASSIFICATION CRITERIA		CPR GUIDE		Securi-Flex®	
FIRE RATING				SFX COMMENT			
Reaction to Fire BS EN ISO 1716						SUBCLASSIFICATIONS FOR EUROCLASSES B _{ca} to D _{ca}	
A _{ca}	Does not contribute to the fire	Due to availability, it will be almost impossible for a cable to meet A _{ca} , so they should only be specified with extreme caution.		(S) SMOKE PRODUCTION	(D) FLAMING DROPLETS	(A) SMOKE ACIDITY	
Reaction to Fire BS EN 50399				BS EN 50399/BS EN 61034-2	BS EN 50399	BS EN 60754-2	
B1 _{ca}	Minimum contribution to the fire	It's highly unlikely the commonly-used cables will be classified to Class B1 _{ca} .		s1a: s1 + transmittance >=80% (BS EN 61034-2)	d0: No fall of droplets or flaming particles, times for 1200 seconds	a1: Very low acidity (conductivity <2.5 μS/mm & pH >4.3)	
B2 _{ca}	Combustible, low flame spread & heat release contribution to the fire	Similar to Class C _{ca} , although a lower acceptable heat release rate and burn measurement. In practice, this is likely to be the highest class cables will meet.		s1b: s1 + transmittance >=60% <80% (BS EN 61034-2)	d1: Fall of droplets or flaming particles that persist for less than 10 seconds, timed for 1200 seconds	a2: low acidity (conductivity <10 μS/mm & pH >4.3)	
C _{ca}	Combustible, moderate flame spread & heat release	This is a more rigorous test than Class D _{ca} , this is widely accepted across Europe as the 'go to' classification, but be aware, many cables do not meet Class C _{ca} though availability is improving.		s1: Low production of slow propagation of smoke	d2: None of the above	d2: None of the above	
D _{ca}	Combustible, moderate flame spread & heat release	This classification has relatively little use or acceptance within specifying/contracting organisations. This is because no large scale fire growth is measured.		s2: Intermediate production & propagation of smoke			
Reaction to Fire BS EN 60332-1-2						Visit us online: www.securiflex.co.uk	
E _{ca}	Combustible, limited fire spread of less than 425mm	A basic test for vertical flame propagation for a single insulated wire or cable using a 1 KW pre-mixed flame. Note: This test does not measure heat release, toxic fumes or smoke.		The Trusted Cable Brand			
F _{ca}	Combustible, fire spread of more than 425mm	Cables classified to Class F _{ca} may have high levels of flammability due to the materials they are made of. This does not mean that the cable cannot be used, it is more likely to be used external.		Classes A to E have to be tested by an independent authorised laboratory. Most cables will fall into classes B2 _{ca} to E _{ca} . For a cable to meet A _{ca} , B1 _{ca} , B2 _{ca} or C _{ca} , there also needs to be regular on-going factory audits.			

OUR OPERATING TEMPERATURE RANGE GUIDE



Securi-Flex®

enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23