

DEFENCE STANDARD CABLE



TITLE:

Defence 7-2 Unscreened LSZH

CODE:


SFX/DS-7-2-6A-LSZH-D-BLK-100

DESCRIPTION:

100m Def Standard 7 x 0.2mm 6 Core Unscreened Black UV LSZH

SUPPLIED AS:

Reel of 100m

































enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23



DEFENCE STANDARD CABLE



Product Specification

Cable Construction

Cable Construction	6 Cores
CPR	Dca -s:2 -a:1 -d:2
Conductor	Tinned Copper
Conductor Diameter (mm)	0.19 ±0.008 x 7(0.2mm²)
Overall Diameter (mm)	5.10 ±0.20

Insulation

Insulation	LSZH
Insulation Colour	Red,Blue,Green,Yellow,White,Black
Insulation Thickness (mm)	0.3

Outer/Jacket Specification

Jacket	UV LSZH
Overall Colour	Black
Overall Diameter (mm)	5.10 ±0.20
Jacket Colour	Black RAL 9005
Jacket Thickness (mm)	0.65
Nylon Rip-Cord	210D

Electrical Characteristics

Max Conductor DC resistance @ 20°C	<39O/km
Rated Temperature (°C)	-40°C to 70°C
Rated Voltage (V)	600V





















enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23



DEFENCE STANDARD CABLE



MORE INFORMATION:

Sorry, no more information is available for this product









enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23









