## **FIRE CABLE**



### TITLE:

FR30 Fire Standard Flame-Flex 60

### CODE:

SFX/FC-2C-1.5-FR60-STD-WHT-500


### **DESCRIPTION:**

500m 2 Core 1.5mm 300/500V White Standard FLAME-FLEX 60

### SUPPLIED AS:

Reel of 500m

- · Can be used both internally and externally in environments where suitable protection is present
- Polymer tape comes away from the sheath when stripping cable
- Low smoke zero halogen plastic is good for use inside public buildings and spaces as will not emit toxic gases if the cable catches fire
- Can be used for emergency lighting applications
- Suitable for instillations where a circuit must be maintained for up to 60 minutes in the event of a fire
- Various lengths in stock





















enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23















# **Product Specification**



### **Cable Construction**

Cable Construction	2 Cores
CPR	LPCB
Conductor	Solid Bare Copper
Overall Diameter (mm)	7.80 ±0.01

### Insulation

Insulation	Silicon Rubber
Insulation Colour	Blue,Brown
Insulation Thickness (mm)	0.70 ±0.02

### **Outer/Jacket Specification**

Jacket	LSZH
Overall Colour	White
Overall Diameter (mm)	7.80 ±0.01
Jacket Colour	White RAL 9010
Jacket Thickness (mm)	0.70 ±0.01

### **Electrical Characteristics**

Rated Temperature (°C)	-30° to +70°
Rated Voltage (V)	300/500V























### **MORE INFORMATION:**

Sorry, no more information is available for this product











enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23









