

FIRE CABLE



TITLE:

FR120 Fire Enhanced Flame-Flex

CODE:

SFX/FC-2C-4.0-FR120-ENH-WHT-1


DESCRIPTION:

1m (per metre) FR120 2 Core 4.0mm 300/500V White Enhanced FLAME-FLEX 120

SUPPLIED AS:

Per 1m Lengths

- · Can be used both internally and externally in environments where suitable protection is present
- Polymer tape comes away from the sheath when stripping cable
- Low smoke zero halogen plastic is good for use inside public buildings and spaces as will not emit toxic gases if the cable catches fire
- High resistance to kinks to protect cables performance
- Suitable for instillations where a circuit must be maintained for up to 120 minutes in the event of a fire
- Can be cut to any length required up to 500m to reduce installation times































Product Specification (CP







Cable Construction

Cable Construction	2 Cores
CPR	LPCB
Conductor	Solid Bare Copper
Overall Diameter (mm)	12.6 ±0.2

Insulation

Insulation	Mica tape covered by extruded LSZH
Insulation Colour	Blue,Brown
Insulation Thickness (mm)	0.90 ±0.02

Outer/Jacket Specification

Jacket	UV LSZH
Overall Colour	White
Overall Diameter (mm)	12.6 ±0.2
Jacket Colour	White RAL 9010
Jacket Thickness (mm)	1.10 ±0.01

Electrical Characteristics

Rated Temperature (°C)	-30° to +70°
Rated Voltage (V)	300/500V











enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23















FIRE CABLE













enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23









