

FIRE CABLE



TITLE:

FR120 Fire Enhanced Flame-Flex

CODE:

SFX/FC-4C-1.5-FR120-ENH-RED-100


DESCRIPTION:

100m FR120 4 Core 1.5mm 300/500V Red Enhanced FLAME-FLEX 120

SUPPLIED AS:

Reel of 100m

- · Can be used both internally and externally in environments where suitable protection is present
- Polymer tape comes away from the sheath when stripping cable
- Low smoke zero halogen plastic is good for use inside public buildings and spaces as will not emit toxic gases if the cable catches fire
- High resistance to kinks to protect cables performance
- Suitable for instillations where a circuit must be maintained for up to 120 minutes in the event of a fire
- Can be cut to any length required up to 500m to reduce installation times





























FIRE CABLE



Product Specification



Cable Construction

Cable Construction	4 Cores
CPR	LPCB
Conductor	Solid Bare Copper
Overall Diameter (mm)	10.50 ±0.01

Insulation

Insulation	Mica tape covered by extruded LSZH
Insulation Colour	Blue,Brown,Black Grey
Insulation Thickness (mm)	0.70 ±0.02

Outer/Jacket Specification

Jacket	UV LSZH
Overall Colour	Red
Overall Diameter (mm)	10.50 ±0.01
Jacket Colour	Red RAL 3000
Jacket Thickness (mm)	0.70 ±0.01

Electrical Characteristics

Rated Temperature (°C)	-30° to +70°
Rated Voltage (V)	300/500V























MORE INFORMATION:

Sorry, no more information is available for this product











enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23









