



## TITLE:

FR30 Fire Standard Flame-Flex 60

## CODE:

SFX/FC-4C-2.5-FR60-STD-RED-500




## DESCRIPTION:

100m 4 Core 2.5mm 300/500V Red  
Standard FLAME-FLEX 60

## SUPPLIED AS:

Reel of 500m

- Can be used both internally and externally in environments where suitable protection is present
- Polymer tape comes away from the sheath when stripping cable
- Low smoke zero halogen plastic is good for use inside public buildings and spaces as will not emit toxic gases if the cable catches fire
- Can be used for emergency lighting applications
- Suitable for installations where a circuit must be maintained for up to 60 minutes in the event of a fire
- Various lengths in stock



enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23



## Product Specification

25-YEAR WARRANTY

### Cable Construction

Cable Construction	4 Cores
CPR	LPCB
Conductor	Solid Bare Copper
Overall Diameter (mm)	12.40 ±0.01

### Insulation

Insulation	Silicon Rubber
Insulation Colour	Blue,Brown,Black Grey
Insulation Thickness (mm)	0.80 ±0.02

### Outer/Jacket Specification

Jacket	LSZH
Overall Colour	Red
Overall Diameter (mm)	12.40 ±0.01
Jacket Colour	Red RAL 3000
Jacket Thickness (mm)	0.80 ±0.01

### Electrical Characteristics

Rated Temperature (°C)	-30° to +70°
Rated Voltage (V)	300/500V



enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23



FIRE CABLE



## MORE INFORMATION:

Sorry, no more information is available for this product

Fire cable



[enquiries@securiflex.co.uk](mailto:enquiries@securiflex.co.uk) | [www.securiflex.co.uk](http://www.securiflex.co.uk) | 03333 44 66 23

TERMS AND CONDITIONS APPLY - WHILE EVERY EFFORT HAS BEEN MADE TO ENSURE THE ACCURACY AND COMPLETENESS OF THE INFORMATION, NO GUARANTEE IS GIVEN NOR RESPONSIBILITY TAKEN FOR ERRORS OR OMISSIONS IN THIS DATA SHEET.

