

BELDEN EQUIVALENTS



TITLE:

OSP Overall Foil Screened Pairs LSZH

CODE:


SFX/OSP4-LSZH-D-GRY-500

DESCRIPTION:

500m OSP4 4pr 24AWG Overall Foil Screen 600V Grey LSZH (9504)

SUPPLIED AS:

Reel of 500m

















enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23

















Product Specification

Cable Construction

Cable Construction	4 Pairs
CPR	Dca -s:2 -a:1 -d:2
Conductor	Tinned Copper
Conductor Diameter (mm)	0.19 ±0.008 x 8(0.20mm²)
Overall Diameter (mm)	6.80 ±0.20

Insulation

Insulation	LSZH
Insulation Colour	Red,Black;White,Black;Green,Black;Blue,Black
Insulation Resistance @20°C	>200MO/km
Insulation Thickness (mm)	0.28

Outer/Jacket Specification

Jacket	LSZH
Overall Colour	Grey
Overall Diameter (mm)	6.80 ±0.20
Jacket Colour	Grey RAL 7042
Jacket Thickness (mm)	0.70

Electrical Characteristics

Insulation Resistance @20°C	>200MO/km
Max Conductor DC resistance @ 20°C	<79.00O/km
Rated Temperature (°C)	-40°C to 70°C
Rated Voltage (V)	600V

























MORE INFORMATION:

Sorry, no more information is available for this product



















