



**CONTROL FLEX**

**Securi-Flex®**

Control flex

**TITLE:**

YY Control Flex LSZH

**CODE:**

SFX/YY-2C-1.5-LSZH-D-GRY-NBR-U-100

**DESCRIPTION:**

100m YY Control Flex 2 Core 1.5mm Grey  
LSZH Numbered Cores

**SUPPLIED AS:**

Reel of 100m



[enquiries@securiflex.co.uk](mailto:enquiries@securiflex.co.uk) | [www.securiflex.co.uk](http://www.securiflex.co.uk) | 03333 44 66 23

TERMS AND CONDITIONS APPLY - WHILE EVERY EFFORT HAS BEEN MADE TO ENSURE THE ACCURACY AND COMPLETENESS OF THE INFORMATION, NO GUARANTEE IS GIVEN NOR RESPONSIBILITY TAKEN FOR ERRORS OR OMISSIONS IN THIS DATA SHEET.

**FLAME-FLEX®** **Drum-Roll®** **LUCKINS®**

**pim**  
partner in motion

**ELECTRICAL**  
**DISTRIBUTORS**  
**ASSOCIATION**

**BASEC**  
MEMBER

**KNX**  
MEMBER

**cai**  
MEMBER

**CPR**  
MEMBER

**UK**  
**CA**



## Product Specification

### Cable Construction

Cable Construction	2 Cores
CPR	Dca
Conductor	Fine Stranded Copper (Class 5)
Conductor Diameter (mm)	1.50
Overall Diameter (mm)	6.6

### Insulation

Insulation	LSZH
Insulation Colour	Black numbered cores

### Outer/Jacket Specification

Jacket	LSZH
Overall Colour	Grey
Overall Diameter (mm)	6.6
Jacket Colour	Grey RAL 7042

### Electrical Characteristics

Max Conductor DC resistance @ 20°C	13.300/km
Rated Voltage (V)	300/500V





CONTROL FLEX

**Securi-Flex®**

### MORE INFORMATION:

Sorry, no more information is available for this product

Control flex



[enquiries@securiflex.co.uk](mailto:enquiries@securiflex.co.uk) | [www.securiflex.co.uk](http://www.securiflex.co.uk) | 03333 44 66 23

TERMS AND CONDITIONS APPLY - WHILE EVERY EFFORT HAS BEEN MADE TO ENSURE THE ACCURACY AND COMPLETENESS OF THE INFORMATION, NO GUARANTEE IS GIVEN NOR RESPONSIBILITY TAKEN FOR ERRORS OR OMISSIONS IN THIS DATA SHEET.

**FLAME-FLEX®** **Drum-ROLL** **LUCKINS®**

**apim**  
accredited partner

**ELECTRICAL**  
DISTRIBUTORS' ASSOCIATION

**BASEC**  
MEMBER

**KNX**  
MEMBER

**cai**  
MEMBER

**CPA**  
MEMBER

**UK**  
**CA**